



US009636512B2

(12) **United States Patent**
Cinbis et al.

(10) **Patent No.:** **US 9,636,512 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **IMPLANTABLE
CARDIOVERTER-DEFIBRILLATOR (ICD)
SYSTEM HAVING MULTIPLE COMMON
POLARITY EXTRAVASCULAR
DEFIBRILLATION ELECTRODES**

(58) **Field of Classification Search**
CPC A61N 1/3918
See application file for complete search history.

(56) **References Cited**

(71) Applicant: **Medtronic, Inc.**, Minneapolis, MN
(US)

U.S. PATENT DOCUMENTS

(72) Inventors: **Can Cinbis**, Salt Lake City, UT (US);
Vladimir P. Nikolski, Blaine, MN
(US); **Jian Cao**, Shoreview, MN (US);
James K. Carney, Roseville, MN (US);
Melissa G. T. Christie, Ham Lake, MN
(US); **Richard J. O'Brien**, Hugo, MN
(US); **Amy E. Thompson-Nauman**,
Ham Lake, MN (US)

4,030,509 A 6/1977 Heilman et al.
4,146,037 A 3/1979 Flynn et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1541191 A1 6/2005
WO 2001023035 A1 4/2001
(Continued)

(73) Assignee: **Medtronic, Inc.**, Minneapolis, MN
(US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

Obadia, et al., "New Approach for Implantation of Automatic
Defibrillators Using Videothoracoscopy", Journal Ann Cardiol
Angeiol (Paris), Sep. 1994; 43 (7) Abstract Only, 1 page.

(Continued)

(21) Appl. No.: **14/932,311**

Primary Examiner — Kennedy Schaetzle

(22) Filed: **Nov. 4, 2015**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2016/0121130 A1 May 5, 2016

Related U.S. Application Data

(60) Provisional application No. 62/075,589, filed on Nov.
5, 2014, provisional application No. 62/075,312, filed
on Nov. 5, 2014.

(51) **Int. Cl.**

A61N 1/39 (2006.01)

A61N 1/362 (2006.01)

A61N 1/05 (2006.01)

(52) **U.S. Cl.**

CPC **A61N 1/3962** (2013.01); **A61N 1/0587**
(2013.01); **A61N 1/3621** (2013.01); **A61N**
1/3987 (2013.01)

This disclosure provides an extravascular ICD system and
method for defibrillating a heart of a patient. The extravas-
cular ICD system includes multiple extravascular electrical
stimulation leads or lead segments located in close proxim-
ity to one another and having respective defibrillation elec-
trodes. The ICD system utilizes the multiple defibrillation
electrodes to form an extravascular electrode vector that
may result a reduction in the shock impedance and/or a
reduction in the DFT compared to extravascular ICD sys-
tems that include only a single extravascular defibrillation
electrode. An ICD of the system may, for example, deliver
a defibrillation shock using an electrode vector in which a
first polarity of the electrode vector is formed by electrically
coupling first and second defibrillation electrodes of first and
second leads, respectively, to the therapy circuitry and a
second polarity of the electrode vector is formed by elec-

(Continued)

